



Rock mechanics of the Callovo-Oxfordian claystone at the Meuse/Haute-Marne Underground Research Laboratory and consequences for CIGEO repository design

G. Armand, A. Noiret, J. Zghondi, R. de La Vaissière, N. Conil, J. Morel, F. Bumbieler

Symposium « Rock Mechanics and Rock Engineering of Geological Repositories in Opalinus Clay and Siltular Claystone »

DRD/MFS/14-0038 © Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS



Legal Framework in France

The 1991 Waste Act

- » Creation of « Andra » as a public independent body
- » 3 research areas for High Level Long-lived Waste: partitioning/transmutation; long term storage; geologic disposal
- **2005: Feasibility assessment of safe geological disposal in Callovo-Oxfordian claystone layer (Meuse/Haute-Marne URL)**

The 2006 Programme Act: Reduce/avoid the burden on future generations


- » Reduce volume and harmfulness of wastes
 - ⇒ SF reprocessing + waste treatment and conditioning
- » Reference option for final waste that can no longer be treated: geological repository with respect to reversibility (100 y at least)
 - Application: 2015; Operation: 2025
- » Continue research on interim storage (Andra) and partitioning/transmutation (CEA) and on a complementary basis.

👉 **Cigéo Project**

DRD/MFS/14-0038 © Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Architecture of CIGEO Project

CIGEO: Industrial Center for Geological Disposal




Underground facility : cells will be added progressively as the operation progresses until they reach a total maximum area of about 15 km², after about 100 years

DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Zoom on the IL-LLW disposal cell




Length: ≈400 m

Excavated diameter: 9-11 m

2x2 or 3x3 packages


No. of containers: 800-1,900

Zoom on the HLW disposal cell



Length $\approx$ 80 m
Diameter: 70 cm
No. of containers: 7-20
(for 40 m)

Package of vitrified waste (CID-V)



Needs in geomechanic

Specific feature of such project

- » Underground nuclear facility
- » Long operational life time
- » Size (length of drift,...)

Need a good understanding of rock and structure interaction

- The Callovo Oxfordien THM behavior
- The structure behavior (concrete,...)
- It is necessary to take into account the consequences of the construction method (velocity of digging, time between digging and installation, type of material as structure)

Design of different elements of the repository

Input for the performance assessment calculation

The performance/safety assessment and technology demonstration are the main objectives of research programs. In geomechanic:

- » To study hydro mechanical behavior of claystone during drift and shaft excavation (short and long term behavior)
 - Impact of digging and support method
 - Orientation of drift
- » To characterize the Excavation Damaged Zone (EDZ)
- » To characterize the Thermo Hydro Mechanical behavior
- » To perform sealing experiments
- » To study the impact of gas transfert in the rock/EDZ/seals

➔ **EDZ characterization for safety assessment calculation**

➔ **HM behavior to design support of the repository drifts**



In situ experiment serve for demonstration issue

In situ measurements are compared with numerical modeling and useful to validate and develop HM model



The Callovo Oxfordian claystone

The Callovo-Oxfordian argillite at the MHM site (Bure)



- Age: 155 million year
- Depth at the site: ~500 m
- Thickness at the site: ~130 m


- Mineralogy: ~ 45% clay + carbonates and silicates
- low water content
- No free water, no water flow
- Diffusive transfer only
- Retention capacity

Rock properties of the COX

Callovo Oxfordian claystone properties at the 490 m level:

- » Mineralogy:
 - 50-55% clay minerals
 - 20-25% carbonate
 - around 25% quartz silts
- » Very low permeability ($5 \cdot 10^{-20} \text{ m}^2$)
- » Short-term behavior, triaxial test: non linear and post-peak depending on σ_3
- » Long term behavior, uniaxial creep test:
 - Creep strain rate increases non-linearly with the applied deviatoric stress
 - Creep rate (Andra 2005):

$$4 \cdot 10^{-12} < \text{creep rate} < 1.60 \cdot 10^{-12}$$
 (test duration 1 to 3 years)
 - Long-term behavior according to the modified Lemaître's model



Rock parameter	Ind.	Value
Bulk specific gravity	ρ	2.39 g/cm ³
Porosity	n	16 ± 2%
Young modulus	$E_{\perp}$	4000 ± 1470 MPa
Poisson Ratio	ν	0.29 ± 0.05
Uniaxial compressive strength	UCS	21 ± 6.8 MPa
Hoek & Brown criteria	S	0.43
	m	2.5
	σ_c (MPa)	33.5
Intrinsic permeability	k	$5 \times 10^{-20} \text{ m}^2$
Water content	w	7.2 ± 1.4 %



HM behavior of drift (at the main level of the URL)



Experimental strategy for the study of drift behaviour

1- Use the underground laboratory for observing real behavior of drift under natural conditions

- » Each drift excavation in the URL is a geomechanical experiment in itself


2- Sequencing of drift construction to highlight the role of support/excavation methods

- » Start with "soft" support drift to study the behavior of COX
- » Skip to rigid support emplaced after a delay of several months
- » Then emplace rigid support sooner after the excavation of the gallery

3- Using parallel drift to compare the different behavior

4- Use mine by experiment (borehole emplaced before the excavation) to study the HM behaviour (at short and long terms)

A huge program of experiments is planned to characterize the response of the rock to different drift construction methods



Excavation methods

» Test different excavations and supports in parallel drifts to better understand the behavior of the drift by comparison (from low support to stiff support like concrete segments)



Road header under shield





GCS drift



GCR drift



BPE drift


radial rockbolts (3 m long),
18 cm of fiber reinforced shotcrete,
12 yieldable concrete wedges (hiDcon®)

≈ GCS drift + 27 cm of concrete
casted in place 6.5 month after
excavation

radial rockbolts (3 m long),
45 cm of fiber reinforced shotcrete
emplaced in four layer

» Segment emplacement method

- Segment of 45 cm thick
- Gap filling with radial injection of mortar



Classical mortar




Compressible mortar
with polystyrene ball


» Experimental set up: “Mine by experiment”

- Boreholes (Displacement, pore pressure) emplaced before excavation
- Convergence measurements, geological survey, boreholes (displacement)
- Borehole to characterize EDZ (permeability measurements, velocity survey,

Around GCS



Around GCR




R LA GESTION DES DÉCHETS RADIOACTIFS

Some example of results on drifts:

Excavation induced fracture

HM behaviour of drift



Fracture orange

Fracture inférieure




Fractures du bombement - extension

❑ 3D scan is performed to map the front face and analyze fracture orientation (GEOTER)



❑ Fractures types are the same in the two directions but number location and extent differ

Structural analysis in an area with numbers of borehole exhibits :

- » Complex pattern
- » Extent of shear fracture is larger than tensile fracture
- » Deep in the rock the shear fracture are visible on different borehole



Type of fracture are similar but the extend depend of drift orientation versus in situ stress state





Drift Orientation		Extensional fractures extent			Shear fractures extent		
		Min.	Average	Max.	Min.	Average	Max.
N65 // σ_h	Ceiling	0.2xD	0.3xD	0.4xD	0.5xD	0.6xD	0.8xD
	Wall	0.1xD	0.1xD	0.2xD	-	-	-
	Floor	0.2xD	0.4xD	0.5xD	0.8xD	0.8xD	1.1xD
N155 // σ_H	Ceiling	-	0.1xD	0.15xD	-	-	-
	Wall	0.01xD	0.2xD	0.4xD	0.7xD	0.8xD	1.0xD
	Floor	-	0.1xD	0.15xD	-	-	-

G. Armand, F. Leveau, C. Nussbaum, R. de La Vaissiere, A. Noiret, D. Jaeggi, P. Landrein, C. Righini, 2014, Geometry and Properties of the Excavation-Induced Fractures at the Meuse/Haute-Marne URL Drifts, Rock mechanics and Rock engineering, Volume 47, Issue 1, pp 21-41

DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Drift GCS (// to σ_H)




- Horizontal convergence is higher the vertical one (ratio of 2,1)
- Velocity decrease as a function of time
- No significant difference between excavated with pneumatic hammer and road header

DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Convergence for drift // σ_h

Drift GED // to to σ_h




- Horizontal convergence is higher the vertical one (ratio of $C_v/C_h = 4$ to 5)
- Velocity decrease as a function of time
- After 1 year, rates $< 10^{-10} \text{ s}^{-1}$



- Convergence depends of the drift orientation
- Highest convergence is observed where the extend of induced fractures is larger

DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS



Location of the boreholes network




19 boreholes (mine by test et SMR)

- 8 extensometers
- 3 inclinometers
- 8 multipacker systems

Horizontal radial displacement

- » Extensometer drilled horizontal from the GAT to the GCS and the last anchor (01) is nearly at the sidewall of the GCS



DRD/MFS/14-0038


© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

- » Steps of excavation are visible:

- 2 spans ahead the front, around 2.4 m
- 7 spans beyond the front face, around 8.4 m. At this distance, the long-term behavior is predominant on the instantaneous strain

Horizontal radial displacement

- » Radial deformation measured in drift GCS has been reanalyzed in order to separate instantaneous and differed response to digging.




- Elastoplastic deformation represents 40%–45% of the total deformation at 90 days, and around 30% at 900 days.
- Farther 5.8 m deep in the rock, differed deformation is very small. The contribution of the far field is about 5% of the total elastoplastic deformation, 4% of the differed deformation at 90 days and less than 1% at 900 days.
- the very small contribution of the far field to the total deformation at the wall exhibits that the differed deformation comes from the near field

DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Pore pressure response (horizontal)


» Multipacker system located oblique horizontal from the GAT to the GCS



- » The distance of influence of the excavation is estimated at 20 m
- » Overpressure of several MPa (3 MPa in chambers 4 at 4.8 m from the GCS wall)
- » Drop of pressure at the front crossing

Pore pressure response (vertical)

» Multipacker system located oblique and rising from the GAT to the GCS



- » Lower overpressures in the vertical direction (1 order of magnitude difference with the horizontal plane)
- » Drop of pressure is observed near the front face and stabilization as a function of the pore pressure gradient
- » Despite the initial stress state is nearly isotropic around the GCS drift, the pore pressure response is anisotropic



HL-LL waste disposal cells

Micro tunnel of 70 cm in diameter

DRD/MFS/14-0038 © Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS



Step by step approach with demonstration and scientific objectives

- » test the making up of the cell (head & usable part)
- » Study the behaviour of the cell under isothermal condition
- » test the making up of different equipments into the cell (base plate, shield steel plug and closing plate),
- » verify the suitable working of the head insert to absorb the thermal dilation of the sleeve,
- » provide data on the casing behaviour under thermal loading,
- » verify the design of the cell head to limit thermal gradients on the drift wall,
- » study the THM behaviour of the interface between rock and casing and of the surrounding rock.


CAC and TEC experiment :smaller scale experiment on steel casing in boreholes

DRD/MFS/14-0038 © Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Andra concept for HL-LL waste disposal cells

Horizontal micro tunnels, about 700 mm in diameter and 100m long, cased with steel sleeves

- » Usable part used for containers disposal,
- » Head part ("insert") 10 m long used for cell sealing
- » End steel plug (base plate), shield steel plug and closing plate



Demonstration program in the URL to test the feasibility of construction and the behaviour of such disposal cells





- » Laser guided auger drilling machine
- » Casing pushed in place during drilling by 2 m long elements welded or socketed to each others
- » Retraction of the machine after excavation


DRD/MFS/14-0038 © Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

ALC experiment

- » Phase 1 (2009): cell of 20 m length
- » Phase 1 bis (2010): cell of 40 m length
- » Phase 2 (2011): cell of 40 m length with sensors on the sleeve
- Insert of 7 m to test emplacement of the head
- » Phase 3.1 (2012): cell of 100 m length




)) Phase 3.2 (2012/2013):



- Full-sized reproduction of a HLW cell (WP3 of EC project LUCOEX) => THM behavior

Main objectives :

- Test the making up
- Verify the design of the cell head to absorb the thermal dilation of the casing and to limit thermal gradients on the drift wall.



DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

Similar shape of fracture pattern at different size (σ_H)



DRD/MFS/14-0038


© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

» Objective (Phase 2)


- Behavior of the void : water arrival versus time
- Behaviour and closure of the void
- Loading of the steel casing
- Test of optical fibers method
- HM behaviour of the micro tunnel



Relative humidity in the void




Convergence of casing




DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS


Experiment in borehole with steel casing (1/2)




t < 60 days
Loading localized in the horizontal direction



60 days < t < 160 days
anisotropic loading $\sigma_h > \sigma_v$




t > 160 days
Decrease of anisotropic loading





- o steel N80 ($\sigma_y = 550$ MPa)
- o Borehole : $\varnothing = 146$ mm
- o casing : $\varnothing_{out} = 143$ mm, thickness = 4,5 mm

DRD/MFS/14-0038

© Andra AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS



Orthoradial deformation at 8 m deep in borehole



Remain in elastic domain, no problem of stability of the casing
But it will contribute to corrosion under stress which is a difficulty for the design of the casing

AGENCE NATIONALE POUR LA GESTION DES DÉCHETS RADIOACTIFS

HL-LL waste disposal cells

The experiment performed at the URL serve to optimize the concept

- » In 2009 the reference length in the concept was 40 m and all cell are parallel to σ_H
 - It was demonstrate that a longer depth could be reached= **now reference length = 80 m**
 - It was confirmed that excavation of cell along σ_H is better than σ_h
- » Elastic deformation in traction have been observed (due to the difference of convergence rate in horizontal and vertical direction) and will contribute to corrosion under stress
 - Backfill the void in between the casing and rock (concrete with bentonite)
 - A test has been performed in November 2013

Experiments in the MHM URL serve to

- » Demonstrate feasibility of a deep geological repository and upscale data obtained on sample (diffusion/retention, permeability,...)
- » Demonstrate the working of the different concept
- » **Optimize** the different concepts
- » Data based to develop/validate model

But you also need

- » Fundamental research to assess the physical process in order to develop model to extrapolate data to the lifetime of a repository
- » Safety calculation to always check if optimization do not decrease the safety
- » At the beginning of the repository construction, final design will be tested in the repository to check in the repository conditions if predicted behavior is observed.

Behavior of the drift

- » Two major phenomena can be distinguished :
 - Elastoplastic and damage mechanisms seems to be predominant at short terms
 - Drift 's deformations develop as a function of time
- » During excavation work, fractures network are induced (mainly shear fracture 75%, extensional fracture 25%)
- » The extend of the fracture network depend on the drift orientation versus the in situ stress field and could not be explain by the anisotropy of the stress field
 - No impact of the method of excavation (BRH versus MAP)
 - Shear fractures (deep in the rock) exhibit low transmissivity
 - With water uptake, fractures transmissivity decreases drastically
- » Anisotropic convergence of the drift are observed :
 - anisotropy of convergence develops in two opposite directions in drifts parallel and perpendicular to σ_H
 - major convergence is measured where the fracture zone is located
- » Differed deformations
 - After one year, deformation rates are in the same velocity range than the one measured on creep test or lower.
 - Most of the differed deformation appears in the fractured zone



Thank you for your attention

Danke Ihnen für Ihre Aufmerksamkeit

Merci pour votre attention

G. Armand, F. Leveau, C. Nussbaum, R. de La Vaissiere, A. Noiret, D. Jaeggi, P. Landrein, C. Righini, 2014, Geometry and Properties of the Excavation-Induced Fractures at the Meuse/Haute-Marne URL Drifts, Rock mechanic and Rock engineering, Volume 47, Issue 1, pp 21-41

G. Armand, A. Noiret, J. Zghondi, D.M. Seyed, 2013, Short- and long-term behaviors of drifts in the Callovo-Oxfordian claystone at the Meuse/Haute-Marne Underground Research Laboratory, Journal of Rock Mechanics and Geotechnical Engineering 5, pp 221-230